

# Wireless Receiver

## Air Hub Analog™

### Model Number

**W141RX**

|                                   |                                                                   |
|-----------------------------------|-------------------------------------------------------------------|
| Description                       | Wireless Receiver with Keypad Controller                          |
| Color Available                   | Black                                                             |
| Product Size                      | 106mm x 105mm x 30mm                                              |
| Package Size                      | 24.5cm x 18cm x 4cm                                               |
| G.W./CTN                          | 10PCS                                                             |
| Certificate                       | FCC ID                                                            |
| Video Format                      | TrueHD / AHD 720P 30fps                                           |
| Connection Type                   | Video Output: GX12-4 Connector<br>Power Input: DTM04-2P Connector |
| Waterproof                        | IP69K                                                             |
| Power Consumption (Heat Chip Off) | 0.35A @12VDC Input Voltage (4.2W)                                 |



### SPECIFICATIONS

|                           |                                                              |
|---------------------------|--------------------------------------------------------------|
| Video Format Output       | TrueHD / AHD                                                 |
| Video Resolution Output   | 720P 30fps                                                   |
| Video Compression         | H.264                                                        |
| Video Channel             | Up to 4 Wireless Cameras (Quad Split-Screen Display)         |
| Antenna                   | External 5dBi Omnidirectional Antenna (SMA Female Connector) |
| Effective RF Range        | 150m (Open area, line-of-sight)                              |
| Operating Frequency       | 2.4GHz (2412 - 2467 Mhz)                                     |
| Image Functions           | Mirror / Flip, Contrast, Brightness, Saturation              |
| Audio                     | Supported                                                    |
| Vibration Rating          | 10G                                                          |
| Reverse Grid Lines        | Yes                                                          |
| Channel Image Orientation | Mirror / Flip (Individual Camera Input Channel)              |
| Supply Voltage            | 12/24V                                                       |
| Operation Temperature     | -20°C~+70°C, RH90%                                           |
| Storage Temperature       | -30°C~+80°C, RH90%                                           |

