

Owner's / Installation Manual

7000 Trailercam Performance Series 2.4GHz RF Wireless Video Monitoring System for Tractor Trailers Rearview Camera



Mounting the Camera

- 1) Select a position to mount the camera that is free of obstructions and moving parts and has a proper viewing angle of the desired area around the vehicle.
- 2) Powerful magnets on the back and or bottom of the camera will attach to any steel surface on the back of the trailer.
- 3) Timer: 15 minutes auto off timer, can be re-started by pressing the power button.
- 4) Wedge shaped shim bracket available (optional, sold separately) when mounting the camera higher on the back of the trailer, looking down.
- 5) Push power button to turn on, once it is paired, camera will stay paired with its monitor, even through power cycles.
- 6) To Pair, start pairing countdown on monitor, push power on camera, once on, push and hold red pairing button until "Save Data" appears on the monitor screen. The Camera image will then appear on the monitor

Maintenance

Although this Rear View Camera requires little care, you can still maintain its condition and performance by following these steps:
* Occasionally clean the camera lens with damp soft cloth.

Should you experience any problem with the camera please refer to the troubleshooting guide below prior to returning your camera for repair. *Note: The user should not attempt to service the unit beyond that described in the operating instructions. All other servicing should be referred to qualified personnel.*

Troubleshooting

Symptoms	Solutions
Cloudy Image	Clean Dirty Camera Lens
No Power / Image	Check Power is on, battery is charged (Power LED is Red when battery is low (9.6VDC)) Pairing indicator is constant green when successfully paired.
LED Red	Low battery indicator, charge the battery

Specifications

Warranty and Support Information

Image Sensor:	1/4" Sony AHD
Resolution (pixels) :	967 x 494
Lens:	f=2.8mm
Lens Angle: H x V	83° x 62°
12pc IR LED:	36ft range
Lux:	0.0 Lux (led on)
TV System:	NTSC
IP Rating:	IP65
DC Power:	12V
Operating Temperature:	-30° ~ 70°
Rechargeable Battery:	Lithium ion
Transmitting Distance ft:	Min 90' clear

Subject to the provisions described below, this CT product is protected for 1 year against defects in material and workmanship. Should a product fail to perform as described above within the warranted period, it will be repaired or replaced with the same or functionally equivalent product by CT. This warrant does not apply if, in the judgement of CT, the product fails due to damage from shipment, handling, storage, accident, abuse or misuse, or if it has been used or maintained in a manner not conforming to product manual instructions, has been modified in any way. Repair by anyone other than CT or an approved agent will void this warranty. The maximum liability of CT under this warranty is limited to the purchase price of the product covered by the warranty. All defective products should be returned to CT with shipping charges pre-paid. CT will not accept collect shipments.